

## AMENDMENTS TO THE SPECIFICATION

1. Please substitute ABSTRACT as follows:

5        An ~~electrostatic discharge (ESD)~~ protection device having reduced trigger voltage is disclosed. ~~A substrate of first conductivity type is provided. A first MOS transistor of second conductivity type is disposed on the substrate. The~~ A first MOS transistor ~~comprises~~ includes a first gate, ~~a first gate dielectric disposed under the first gate,~~ a first heavily doped region ~~of the second conductivity type implanted into the~~ substrate at one side of the first gate, and a second heavily doped region ~~of the second conductivity type implanted into the substrate at the other side of the first gate.~~ A second MOS transistor ~~of the second conductivity type~~ is laterally disposed ~~on the substrate~~ in proximity to the first MOS transistor. The second MOS transistor ~~comprises~~ includes a second gate, ~~a second gate dielectric disposed under the second gate,~~ a third heavily doped region ~~of the second conductivity type implanted into the~~ substrate at one side of the second gate, and a fourth heavily doped region ~~of the second conductivity type implanted into the substrate at the other side of the second gate.~~ ~~At least one floating gate MOS transistor comprising a floating gate dielectric is formed on the substrate. A floating gate overlies the floating gate dielectric. The~~ floating gate MOS transistor is located between the first ~~MOS transistor and the~~ second MOS transistors. [The] A floating gate MOS transistor is serially connected to the first MOS transistor via the second heavily doped region and is serially connected to the second MOS transistor via the third heavily doped region.

25